

2021 SOR Single Temp Trailer

Outline Dimensions:

External Length:	13600mm	Internal Length:	13355mm
External Width:	2600mm	Internal Width:	2470mm
Overall Height:	4040mm*	Internal Height:	2600mm



Year: 2021

Manufacturer: SOR

Axle: BPW Tri-Axle on Air Suspension

Trailer Type: Refrigerated

CHASSIS AND RUNNING GEAR

Chassis Model

- **Flat Chassis SP71 Model**
- **Chassis and Wheel Hubs Painted Jet Black**
- Wheel Base Suitable for 44T Operation
- EU Type Approval with Certificate of Conformity

Coupling and Connections

- **Standard UK C-Type Couplings fitting on sliding suzie rail**
- 12mm Reinforced Rubbing Plate

Kingpin

- 15T Rated Kingpin Positioned at 1600mm

Axles

- **BPW Tri-Axle on Air Suspension**
- **Front Lift Axle**



Braking

- **Drum Brakes** 42cm x 18cm with Spring Brake Chambers fitted to all Axles
- WABCO EBS 2S/2M with Anti-Roll Stability Program
- WABCO Park and Shunt Valves fitted to N/S Landing Legs
- Raise/Lower Valve complete with Auto-Reset fitted to N/S rear

Wheels and Tyres

- ALCOA Dura-Bright Alloy Wheels with 385/65 R22.5 Bridgestone Tyres

Landing Gear

- JOST Modul Landing Legs with Flat Compensating Feet

Sideguards

- 1 Vertical and 2 Horizontal Aluminium Profiles
- 2 Galvanised Full-Width Supports

Spray Suppression

- Wing and Valance System with SOR Logo Spray Flaps
- Rear Spray Flap mounted on Under Run Bar with SOR Logo

Under Run Bar

- Standard Square Profile Under Run Bar

Ferry Securing

- 6 x Ferry Rings

Rear Protection

- 6 Horizontal Black SOR Dock Buffers
- 2 Vertical Black SOR Dock Buffers
- **Galvanised Double Compression Rollers**





01785 848 258
sales@barkerscommercials.com
www.barkerscommercials.com

BODY

Body Model

- SP71TS60X GRP Skin Body with Provisional ATP & Full UK Certification

Sidewall Thickness

- 60mm Sidewall Thickness (2470mm Internal Width)

BODY (INTERNAL)

Floor

- Full Aluminium Pechiney Low-Noise Floor
- Extended Rear Frame Threshold into Floor
- 125mm Floor Thickness

Load Lock Track

- 2 Rows Recessed 1806 Loadlok (800mm & 1600mm)

Internal Sidewall Protection

- 450mm (250mm+200mm) Internal Pallet Protection from floor

Roof and Internal Lighting


- 95mm Roof Thickness
- 3 x LED Internal Lights with Rear Motion Sensor

Load Partition

- CBF Mattress type internal door

Evaporator Guard(s)

- 7 Pillar Grid Evap Guard
- **L-Profile Rear Evap Guard**



01785 848 258
sales@barkerscommercials.com
www.barkerscommercials.com

BODY (EXTERNAL)

Front Bulkhead Corner Protection

- Top and Bottom Stainless Steel Corner Protectors

Marker Lights

- 4 x White LED Marker Lights on Front Bulkhead (1 per corner)
- **6 x Side LED Marker Lights Per Side**
- 1 x Multi-Function Marker Light Per Corner of Rear Frame
- 4 x Additional Standard Red Top Frame LED Marker Lights (6 in total)
- Side Markers with Indicating Functionality

Rear Chamber Lights

- Recessed Triple Lucidity Hamburger LED Lights with 1 x Fog and 1 x Reverse Per Side
- 1 x LED Stalk Light Per Side

Rear Closure

- Heavy Duty, Impact Resistant 3mm Gauge Stainless Steel Rear Frame with Additional 3mm Reinforcement at Corners
- Standard Barn Doors fitted with Push-Lock Handles
- Doors Supplied with 250mm Internal Pallet Protection

Rear Access

- SOR Heavy-Duty Triple Step with Shelf Access Ladder

Finish & Livery

- No Livery or Fleet Numbers

REFRIGERATION UNIT

- Carrier HE19 System 2
- Datacold 300